

Han 10A-AK-LB (Schnur fuer Pg 13,5/16)



Image is for illustration purposes only. Please refer to product description.

Part number	09 20 010 5423
Specification	Han 10A-AK-LB (Schnur fuer Pg 13,5/16)
HARTING eCatalogue	https://b2b.harting.com/09200105423

Identification

Category	Accessories
Series of hoods/housings	Han A [®]
Type of hood/housing	Protection cover for hoods
Description of hood/housing	Metal With fixing cord
Type	Low construction High construction

Version

Size	10 A
Locking type	Single locking lever
Han-Easy Lock [®]	Yes

Technical characteristics

Limiting temperature	-40 ... +125 °C
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4 4X 12

Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated



Pushing Performance
Since 1945

Material properties

Material (locking)	Polycarbonate (PC) Stainless steel
Colour (locking)	RAL 7037 (dust grey)
Material flammability class acc. to UL 94 (locking levers)	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R1 (HL 1-3) R7 (HL 1-3)

Specifications and approvals

Approvals	DNV GL
-----------	--------

Commercial data

Packaging size	1
Net weight	75 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140039551
eCl@ss	27440208 Cap for industrial connectors