



**Special features**

- Robust housing
- Flicker-free
- Short-circuit-proof, overload protection, overheating protection
- Compact design

|  |   |
|--|---|
| <b>Housing Material</b>                    | Aluminium                               |
| <b>Housing Color</b>                       | Grey                                    |
| <b>Operating Mode</b>                      | Constant voltage                        |
| <b>Protection Class</b>                    | Protection class I/protective grounding |
| <b>Power</b>                               | 150 W                                   |
| <b>Output Voltage</b>                      | 24 V/DC                                 |
| <b>Output Current</b>                      | 0-6250 mA                               |
| <b>Power Factor</b>                        | 0.98                                    |
| <b>Connection Type</b>                     | Open cables                             |
| <b>Primary Connection</b>                  | With free strand / conductor ends       |
| <b>Secondary Connection</b>                | Open cables                             |
| <b>Number of Circuit Breaker B10A max.</b> | 2                                       |
| <b>Number of Circuit Breaker B16A max.</b> | 4                                       |
| <b>Number of Circuit Breaker C10A max.</b> | 6                                       |
| <b>Number of Circuit Breaker C16A max.</b> | 9                                       |
| <b>Inrush Current max.</b>                 | 60 A / 300 µs                           |
| <b>Capacitive Load</b>                     | 626.3 nF                                |
| <b>Reference Point Tc</b>                  | 80 °C                                   |
| <b>Working Temperature</b>                 | -20 to 50 °C                            |
| <b>Storage Temperature</b>                 | -20 to 70 °C                            |
| <b>IP Protection Class</b>                 | IP 67                                   |
| <b>Life Time</b>                           | 50000 h                                 |
| <b>Length</b>                              | 191 mm                                  |
| <b>Width</b>                               | 70 mm                                   |
| <b>Height</b>                              | 40 mm                                   |
| <b>Product weight</b>                      | 889 g                                   |

