


Matric-F3

Recessed mounted light line, mounting brackets incl - Direct light distribution

Article code: LF3AEL-830M-L1198



Illustrations may only be similar and serve as an orientation.


Matric-F3. LED. Recessed mounted light line with surrounding frame for installation in sawn wall and ceiling with cut-out openings. Mounting brackets included. Luminaire body made of high-quality aluminum profile. Surface finish Silver Anodised. Direct only light distribution.

70mm. H=75mm. Medium-power current. 2066lm. 21W. 3kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 and 50001:2018 certified.

Matric-F3


Recessed mounted light line, mounting brackets
incl - Direct light distribution

Article code: LF3AEL-830M-L1198




Customer / Project: _____

Note: _____






d tuc ttc tÜc ttc t¼c t-c t ~c t,,c ttc tdc tPc t@c t0c t
c t



Matric-F3

Recessed mounted light line, mounting brackets
incl - Direct light distribution

Article code: LF3AEL-830M-L1198



Customer / Project: _____

Note: _____

c tñb to b tñb tColour temperature: 3000K (Warm White).
Colour Rendering Index (CRI): >80. Microprismatic screen for
uniform illumination and reduced luminance in office areas.
Dimmable DALI. LxWxH (rectangular). L=1198mm. W=





Matric-F3

Recessed mounted light line, mounting brackets
incl - Direct light distribution

Article code: LF3AEL-830M-L1198

Customer / Project: _____

Note: _____



Productname	Matric-F3
Lamp	LED
Installation Type	Recessed mounted light line, mounting brackets incl
Surface finish	Silver Anodised
Light characteristics	Direct light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Microprismatic screen
Control	Dimmable (DALI)
Length L/Diameter D (mm)	L=1198mm
Width W (mm)	W=70mm
Height H (mm)	H=75mm
Current/Power	Medium-Power
Luminous Flux	2066lm
Power consumption	21W
Degree of protection	IP20
Certification	Prüfzeichen: ENEC
LED lifetime	L85B10 (tq 25°C) = 50.000h
Photometric code	8 30 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	3kg

