



A spotlight with that certain something: Thanks to the acrylic ring, the COB 68 acrylic not only emits light downwards but also softly to the side. The resulting light pattern on the ceiling subtly yet effectively draws the eye and creates a cosy ambience that permeates each space.

Special features

- Ring made from acrylic glass
- Subtle side lighting
- High colour reproduction value

Housing Material	Aluminium
Housing Color	Silver
Material of Lens	PMMA
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant current
Rated Input	6.5 W
Rated Input Voltage	18-20 V/DC
Rated Current	350 mA
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Secondary Cable Length	0.3 m
Dimmable	Yes
Control technology	Dimmable via optional power supply unit
Motion Detector	No

Installation Depth	50 mm
Cut Out Diameter	62 mm
Product weight	204 g
Working Temperature	-5 to 40 °C
Storage Temperature	-25 to 40 °C
IP Protection Class	IP 20
Life Time L70 / B50	30000 h
Switching Cycles	50000
Power Consumption	7 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Color Temperature	2700 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	675 lm
Luminous Efficiency	103.8 lm/W
Rated Angle of Reflection	30 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Length	78 mm
Height	53.5 mm
Diameter	78 mm