



鸿伟能源有限公司
Howell Energy Co., Ltd.

Add: B1010, Genzon Times Square, Longgang Center, Shenzhen, China
Tel: +86 755 89335456 Fax: +86 755 89335457

Website: <http://www.howellenergy.com> Email: info@howellenergy.com

MATERIAL SAFETY DATA SHEET (MSDS)

(According to EEC Directive 93/112/EC)

Production of MSDS proving UN manual of Tests and Criteria, Part III, sub-section 38.3 is met

**The International Air Transport Association (IATA) Dangerous Goods Regulations
(57th Edition)**

Date Of Preparation: Jan. 4th, 2016

1 - Identification of the product and the supplier

1.1 Product: Lithium battery

Product Category: Lithium Ion Batteries

Electrodes	Negative Electrode: Carbon	Positive Electrode Lithium cobaltite (LiCoO ₂)
Electrolyte	Solution of lithium hexafluorophosphate (LiPF ₆) in a mixture of organic solvents	
Nominal voltage	14.8 Volts	

Equivalent name: lithiated cobalt oxide.

Ethylene Carbonate (EC) + DiMethyl Carbonate (DMC) + DiEthyl Carbonate (DEC).

1.2 Manufacturer:

Howell Energy Co., Ltd
B1010, Genzon Times Square, Longgang Center
Shenzhen China 518112
Tel: +86-755-89335456
Fax: +86-755-89335457
Web: www.howellenergy.com
Email: info@howellenergy.com



2 - Composition (Typical weight percentages of basic material)

Metals	%	Others	%
Copper,	5~15	Lithium cobalt oxide	25~50
Aluminum	2~10	Carbon	10~30
Lithium ion	2~3	Organic solvents	10~20
Aluminum packing foil	5~15	Polyvinylidene Fluoride (PVDF)	0~5
Nickel	0.5~5		

3 - Hazards Identification

3.1 Physical:

The so-called Li-ion polymer battery is evolved from common liquid Li-ion battery by using LiCoO₂ at anode, carbon at cathode, and

polymer foil as electrolyte, eventually put these materials into a pouch shape aluminum plastic film package. Li-ion polymer battery is the new generation Lithium battery that has made significant milestones in battery's development. The obvious advantage of the Li-ion polymer battery not only has its high capacity, long cycle life, steady discharge rate and non-pollution, but also eliminates safety hazards that liquid Li-ion battery exists, especially of those steel can batteries. Furthermore, the flexible outline and custom design shape is more convenient at fingertips in a timely and cost effective way.

3.2 Chemical:

Classification of dangerous substances contained into the products per directive 67/548/EEC

Substance		Melting point	Boiling point	Classification			
CAS N°	Chemical Symbol			Exposure Limit	Indication of danger	Special Risk (1)	Safety Advices (2)
12190-79-3	LiCoO ₂	> 1000°C	N/A	0.1 mg/m ³ OSHA		R22 R43	S2 S22 S24 S26 S36 S37 S43 S45
EC: 96-49-1 DMC: 616-38-6 DEC: 105-58-8	Organic Solvents (EC-DMC DEC)	EC: 38°C DMC: 4°C DEC: -43°C	EC: 243°C DMC: 90°C DEC: 127°C	None Established OSHA	Flammable	R21 R22 R41 R42/43	S2 S24 S26 S36 S37 S45
21324-40-3	LiPF ₆	N/A (Decomposes at 160°C)	N/A	None established OSHA	Irritant Corrosive	R14 R21 R22 R41 R43	S2 S8 S22 S24 S26 S36 S37 S45

3.2.1 – Nature of special risks :

- R 14 Reacts with water.
- R 21 Harmful in contact with skin.
- R 22 Harmful if swallowed.
- R 41 Risk of serious damage to the eye.
- R 42/43 May cause sensitization by inhalation and skin contact.
- R 43 May cause sensitization by skin contact.



3.2.2 – Safety advises:

- S 2 Keep out of reach from children.
- S 8 Keep away from moisture.
- S 22 Do not breathe dust.
- S 24 Avoid contact with skin.
- S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical attention.
- S 36 Wear suitable protective clothing.
- S 37 Wear suitable gloves.
- S 45 In case of incident seek medical attention.

4 - First Aid Measures

In case of battery rupture or explosion, evacuate personnel from contaminated area and provide maximum ventilation to clear out fumes/gases. In all case, seek medical attention.

- Eye Contact: Flush with plenty of water (eyelids held open) for at least 15 minutes.
- Skin Contact: Remove all contaminated clothing and flush affected areas with plenty of water and soap for at least 15 minutes.
- Do not apply greases or ointments.
- Ingestion: Dilute by giving plenty of water and get immediate medical attention.
- Assure that the victim does not aspirate vomited material by use of positional drainage.
- Assure that mucus does not obstruct the airway.
- Do not give anything by mouth to an unconscious person.

- Inhalation: Remove to fresh air and ventilate the contaminated area.
- Give oxygen or artificial respiration if needed.

5 - Fire-Fighting Measures

- Fire and explosion hazard: The batteries can leak and/or spout vaporized or decomposed and combustible electrolyte fumes in case of exposure above 60°C resulting from inappropriate use or from the environment.
- Possible formation of hydrogen fluoride (HF) and phosphorous oxides during fire. LiPF₆ salt contained in the electrolyte releases hydrogen fluoride (HF) in contact with water.
- Extinguishing media: Suitable: CO₂, Dry chemical or Foam extinguishers
- Not to be used: Type D extinguishers
- Special exposure hazards: Following cell overheating due to external source or due to improper use, electrolyte leakage or battery container rupture may occur and release inner component/material in the environment.
- Eye contact: The electrolyte solution contained in the battery is irritant to ocular tissues.
- Skin contact: The electrolyte solution contained in the battery causes skin irritation.
- Ingestion: The ingestion of electrolyte solution causes tissue damage to throat and gastro/respiratory tract.
- Inhalation: Contents of a leaking or ruptured battery can cause respiratory tract, mucus, membrane irritation and edema.
- Special protective equipment: Use self-contained breathing apparatus to avoid breathing irritant fumes. Wear protective clothing and equipment to prevent body contact with electrolyte solution.

6 - Accidental Release Measures

The material contained within the batteries would only be expelled under abusive conditions. Using shovel or broom, cover battery or spilled substances with dry sand or vermiculite, place in approved container (after cooling if necessary) and dispose in accordance with local regulations

7 - Handling And Storage

The batteries should not be opened, destroyed nor incinerate since they may leak or rupture and release in the environment the ingredients they contain.

Handling:

- Do not crush, pierce, short (+) and (-) battery terminals with conductive (i.e. metal) objectives.
- Do not directly heat or solder.
- Do not dispose of fire.
- Do not mix batteries of different types and brands.
- Do not mix new and used batteries.
- Keep batteries in non-conductive (i.e. plastic) trays.
- Do not strike or throw the battery against hard surface.
- Do not directly solder the battery and pierce the battery with a nail or other sharp object.



Storage:

- Store in a cool (preferably below 30°C) and ventilated area away from moisture, sources of heat, open flames, food and drink.
- Keep adequate clearance between walls and batteries.
- Temperature above 70°C may result in battery leakage and rupture.
- Short circuit can cause burn, leakage and rupture hazard, keep batteries in original packaging until use and do not jumble them.
- Others: Follow HOWELL ENERGY's recommendations regarding maximum recommended currents and operating temperature range.
- Applying pressure or deforming the battery may lead to disassembly followed by eye, skin and throat irritation.

8 - Exposure Controls / Personal Protection

- Respiratory protection: *Not necessary under normal use*. In case of battery rupture, use self-contained full-face respiratory

equipment.

- Hand protection: *Not necessary under normal use.* Use Viton rubber gloves if handling a leaking or ruptured battery.
- Eye protection: *Not necessary under normal use.* Wear safety goggles or glasses with side shields if handling a leaking or ruptured battery.
- Skin protection: *Not necessary under normal use.* Use rubber apron and protective working in case of handling of a ruptured battery.

9 - Physical And Chemical Properties

9.1 Appearance:

(Physical shape and color as supplied) Metal squares, hermetically sealed and fitted with an external plastic box.

9.2 Temperature range:

	Continuous	Occasional
In Storage	-20/+35°C	-20/+45°C
During Discharge	-20/+ 60°C	- 20/+ 60°C
During Charge	0/+ 45°C	0/+ 45°C

9.3 Specific energy:

≈ 135 Wh/kg (Note: Wh = Nominal voltage x Rated Ah as defined in IEC standard N° 285. kg = Average battery weight)

9.4 Specific pulse power:

≈ 300 Wh/kg

9.5 Mechanical resistance: As defined in relevant IEC standard

9.6 Others:

10 - Stability and Reactivity

Conditions to avoid:

- Heat above 70°C or incinerate.
- Deform, mutilate, crush, pierce, and disassemble.
- Short circuit.
- Prolonged exposure to humid conditions.

Materials to avoid: N/A.

Hazardous decomposition products: Corrosive/Irritant Hydrogen fluoride (HF) is produced in case of reaction of lithium hexafluorophosphate (LiPF₆) with water. Combustible vapors and formation of Hydrogen fluoride (HF) and phosphorous oxides during fire.

11 - Toxic Information

HOWELL ENERGY Li-ion polymer rechargeable batteries do not contain toxic materials.

12 - Ecological Information

When properly used or disposed, Howell Lithium-Ion rechargeable batteries do not present environmental hazard.

13 - Disposal Considerations

Dispose in accordance with applicable regulations that vary from country to country. (In more countries, the thrashing of used batteries is forbidden and the end-users are invited to dispose them properly, eventually through not-for-profit organizations, mandated by local governments or organized on a voluntary basis by professionals). Li-ion polymer batteries should have their terminals insulated and be preferably wrapped in plastic bags prior to disposal.

13.1 Incineration:



Incineration should never be performed by battery users but eventually by trained professionals in authorized facilities with proper gas and fumes treatment.

13.2 Land filling: Leachability regulations (mg/l)

Component	Leachability	EC limit	EPA	Other*
Iron	100	2		5
Nickel	500			0.5

13.3 Recycling: Send to authorize recycling facilities, eventually through licensed waste carrier.

14 - Transport Information

14.1 United Nations:

- UN° 3480
- Classification 9
- Packaging ICAO 903 for Air Transport
- IMDG 903 for Sea Transport
- UN38.3 for Air Transport

14.2 International Conventions:

- Air IATA Yes
- Sea IMDG Yes
- Land ADR (road) Yes
- RID (rail) Yes



With Reference to the IATA Dangerous Goods Regulations 57th Edition, I declare the following information are accurate and comply in all respects with Governments and IATA restricted article regulations. The Lithium-Ion or Lithium Polymer cells and batteries are compliant with UN38.3 Test Requirements and do not contain any recalled/defective cells /batteries as per Special Provision A154. This consignment can be shipped as “ Not Restricted” cargo in accordance with IATA Dangerous Goods Regulations Section II of Packing Instruction PI965-967.

14.3 Others:

In the USA: Code of Federal Regulations (49 CFR Ch. 1 § 173-185)

15 - Regulation Information

The transport of rechargeable lithium-ion polymer batteries is regulated by various bodies (IATA, IMO, ADR, US-DOT) that follow the United Nations "Recommendations on the Transport of Dangerous Goods, Model Regulations, 15th Revised edition - 2011 - Ref. ST/SG/AC.10/1/Rev.15.

Depending on their lithium metal equivalent weight content, design, and ability to pass safety tests defined by the UN in the "Recommendations on the Transport of Dangerous Good - Manual of Tests and Criteria - 3rd Revised edition - 2002 - Ref. ST/SG/AC.10/11 Rev.3 Amendment 1 "Lithium Batteries", the lithium-ion cells and the battery packs may or may not be assigned to the UN N° 3090 Class-9, that is restricted for transport.

Individual lithium-ion cells and battery packs with respectively less than 1.5 and 8 grams of equivalent lithium metal content that pass the UN-defined safety tests, are not restricted for transport (4 .2 Ah of declared nominal capacity=0.3 gram Li equivalent weight content).

16 - Other Information / Disclaimer

This information has been compiled from sources considered to be dependable and is, to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty (either expressed or implied) or guarantee is made to the accuracy, reliability or completeness of the information contained herein.

This information relates to the specific materials designated and may not be valid for such material used in combination with any other materials or in any process. It is the user's responsibility to satisfy himself as to the suitability and completeness of this information for his particular use.

HOWELL ENERGY does not accept liability for any loss or damage that may occur, whether direct, indirect, incidental or consequential, from the use of this information. HOWELL ENERGY does not offer warranty against patent infringement. Additional information is available by calling the telephone number above designated purpose.