



<b>Housing Material</b>	Copper	<b>Switching Cycles</b>	100000
<b>Housing Color</b>	Black	<b>Power Consumption</b>	38 kWh/1000h
<b>Protection Class</b>	Protection class II/protective insulation	<b>Energy Efficiency Class</b>	G
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz		
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Cable Primary</b>	Yes		
<b>Primary Connection</b>	Power plug		
<b>Dimmable</b>	Yes		
<b>Control technology</b>	RF 2,4 GHz		
<b>Number of Channels</b>	4		
<b>Light Source</b>	LED, Light source not changeable		
<b>Lightcolor</b>	RGB/warm white		
<b>Color Temperature</b>	2700 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	90		
<b>Rated Angle of Reflection</b>	120 Degree		
<b>Distribution Characteristic 120°</b>	DLS		
<b>Total Length to be Operated max.</b>	5 m		
<b>Segment Length</b>	166 mm		
<b>Segment LED Quantity</b>	14		
<b>LED Distance</b>	12		
<b>Length</b>	2500 mm		
<b>Width</b>	10 mm		
<b>Height</b>	3 mm		
<b>Product weight</b>	325 g		
<b>Working Temperature</b>	-5 to 40 °C		
<b>Storage Temperature</b>	-10 to 50 °C		
<b>IP Protection Class</b>	IP 20		
<b>Life Time L70 / B50</b>	30000 h		