



Special features

- Including 0.5 m connecting cable

Housing Material	Stainless steel, Die-cast aluminium
Housing Color	Silver
Material of Lens	Glass
Protection Class	Protection class I/protective grounding
Rated Input	7.7 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Cable Primary	Yes
Primary Connection	Connection box
Primary Cable Length	0.5 m
Dimmable	No
Motion Detector	No

Product weight	1180 g
Working Temperature	-20 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 67
Load Force max.	20 kN

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	5 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	700 lm
Luminous Efficiency	90.9 lm/W
Rated Angle of Reflection	25 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Life Time L70 / B50	30000 h
Switching Cycles	100000
Power Consumption	8 kWh/1000h
Energy Efficiency Class	E

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Top

Length	125 mm
Width	125 mm
Height	75 mm
Installation Depth	95 mm
Cut Out Length	112 mm
Cut Out Width	112 mm