



TAYGETA series outdoor lights catch the eye and use their angled housing shape purposefully to illuminate paths, walls and objects on both sides from different angles. Available in two sizes [60 cm and 100 cm], the TAYGETA 1000 is optionally also available with integrated, energy-saving movement and twilight sensor.

Special features

- Base L x W x H: 220 x 90 x 10 mm

Housing Material	Die-cast aluminium	IP Protection Class	IP 65
Housing Color	Grey	Life Time L70 / B50	30000 h
Material of Lens	Plastic	Switching Cycles	15000
Protection Class	Protection class I/protective grounding	Power Consumption	18 kWh/1000h
Rated Input	18 W	Energy Efficiency Class	G
Rated Input Voltage Frequency	110-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Cable Primary	Yes		
Primary Connection	Connection box		
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	1500 lm		
Rated Angle of Reflection	110 Degree		
Distribution Characteristic 120°	NDLS		
Light Exit Surfaces	2		
Light characteristics	Direct		
Light direction	Below, Rear		
Length	220 mm		
Width	148 mm		
Height	600 mm		
Base length	220 mm		
Base width	90 mm		
Base height	10 mm		
Working Temperature	-5 to 40 °C		
Storage Temperature	-10 to 60 °C		