

Art no	373501	373502	373503	373504	373603	373604	373606	373609	373607
									
Description	A60 FILAMENT 470LM 4W E27	A60 FILAMENT 806LM 6,0W E27	A60 FILAMENT 1060LM 8W E27	A67 FILAMENT 1520LM 12W E27	B35 CANDLE FILAMENT 250LM 2,3W E14	B35 CANDLE FILAMENT 470LM 4W E14	P45 BALL FILAMENT 250LM 2W E14	P45 BALL FILAMENT 470LM 4W E14	P45 BALL FILAMENT 250LM 2,3W E27
Lamp power (W)	4	6	8	12	2,3	4	2	4	2,3
Nominal voltage (V)	220-240V 50/60 Hz	220-240V 50/60 Hz	220-240V 50/60 Hz	220-240V 50/60 Hz	220-240V 50/60 Hz	220-240V 50/60 Hz	220-240V 50/60 Hz	220-240V 50/60 Hz	220-240V 50/60 Hz
Supply current (mA)	38mA	50mA			25mA	38mA	25mA	36mA	25mA
Inrush current									
Rated lifetime (h) L70B50	15000	15000	15000	15000	15000	15000	15000	15000	15000
Number of start-up cycles	40000	40000	40000	40000	40000	40000	40000	40000	40000
Color temperature (K)	2700	2700	2700	2700	2700	2700	2700	2700	2700
Run-up time 60% lumen (s)	<0,5	<0,5	<0,5	<0,5	<0,5	<0,5	<0,5	<0,5	<0,5
Dimmable	No	No	No	No	No	No	No	No	No
Comparison incandescent lamp (W)	40	60	75	100	25	40	25	40	25
Mercury content (mg)	0	0	0	0	0	0	0	0	0
Luminous flux (lm)	470	806	1060	1520	250	470	250	470	250
Lm/W (lm)	118	134	133	127	109	118	125	118	109
Lumen maintenance rated lifetime (%)	70	70	70	70	70	70	70	70	70
Power factor	>0,4	>0,5	>0,5	>0,5	>0,7	>0,4	>0,7	>0,4	>0,7
Start-up time (s)	<0,5	<0,5	<0,5	<0,5	<0,5	<0,5	<0,5	<0,5	<0,5
Beam angle (°)	320°	320°	320°	320°	320°	320°	320°	320°	320°
Ra-index	>80	>80	>80	>80	>80	>80	>80	>80	>80
Energy class	E	E	E	E	F	E	E	E	F
Energy consumption (kwh/1000h)	4,2	6	8	12	2,6	4	2,6	4	2,6
Ambient temperature	-20°C - +40°C	-20°C - +40°C	-20°C - +40°C	-20°C - +40°C	-20°C - +40°C	-20°C - +40°C	-20°C - +40°C	-20°C - +40°C	-20°C - +40°C
Max lamp length (mm)	105	105	105	123	98	98	78	78	76
Max lamp diameter(mm)	60	60	60	60	35	35	45	45	45
Bulb diameter (mm)	60	60	60	60	35	35	45	45	45
Bulb/lamp material	Glass	Glass	Glass	Glass	Glass	Glass	Glass	Glass	Glass
Base	E27	E27	E27	E27	E14	E14	E14	E14	E27
Packaging unit (pcs)	10	10	10	10	10	10	10	10	10
Lamp weight gross (g)	32	33	34	39	16	16	16	16	16