



Special features

- Very low glare value
- Service life 50,000 h L80B10
- Dimmable using rotary switch
- Ready to use including 2.5 m connecting cable

Housing Material	Aluminium
Housing Color	Silver
Material of Lens	Acryl
Colour of Lens	White
Protection Class	Protection class I/protective grounding
Rated Input	80 W
Rated Input Voltage	200-240 V/AC 50 / 60 Hz
Frequency	
Power Supply Unit incl.	No
Connection Cable Primary	Yes
Primary Connection	Power plug
Primary Cable Length	2.5 m
Connection Type According to Standard	Typ Y
Dimmable	Yes
Control technology	Touch-Sensor
Motion Detector	No

Length	610 mm
Width	280 mm
Height	1950 mm
Product weight	14000 g
Working Temperature	-20 to 45 °C
Storage Temperature	-40 to 80 °C
IP Protection Class	IP 20
Life Time L70 / B50	50000 h
Life Time L80 / B10	50000 h
Switching Cycles	25000
Power Consumption	80 kWh/1000h
EEI	E

Light Source	LED, Light source not changeable
Lightcolor	Neutral white
Color Temperature	4000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	8300 lm
Luminous Efficiency	103.8 lm/W
Rated Angle of Reflection	110 Degree
Rated Angle of Reflection 2	90 Degree
UGR	19
Distribution Characteristic 120°	DLS
Light Exit Surfaces	2
Light characteristics	Direct
Light direction	Top, Below

