

Datenblatt Art. 919.284

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

PRCD Adapter

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung	16A / 250V~	Rated current / rated voltage	16A / 250V~
Frequenz	50Hz	Frequency	50Hz
Anschlussleistung	3680W	Connected load	3680W
Netzanschluss		Power supply	
Stecker	CEE 7/7 (Type E/F)	Plug	CEE 7/7 (Type E/F)
Stromausgang		Power output	
Steckdosen	Socket outlets		
1x CEE 7/3 (Type F)	1x CEE 7/3 (Type F)		
2-polig mit Schutzkontakt	2-pole with earthing contact		
Mit erhöhtem Berührungsschutz	With shutter		
weiß, mit Klappdeckel,	white, with hinged lid,		
16A / 250V~, IP44	16A / 250V~, IP44		
Schutzeinrichtungen		Protective devices	
PRCD	PRCD		
ohne Schutzleiterüberwachung	without protective conductor monitoring		
Abschaltung 2-polig (L, N)	2-pole interrupt (L, N)		
mit Unterspannungsauslösung	with undervoltage tripping		
Auslösestrom < 30mA	Tripping current < 30mA		
Auslösezeit < 30mS	Tripping time < 30mS		
Weitere Produkteigenschaften		Further product attributes	
Material	Material		
Gehäuse:	Housing:		
PA6 GF30 850°C, weiß	PA6 GF30 850°C, weiß		
Lieferumfang	Scope of delivery		
1x PRCD Adapter	1x PRCD Adapter		
in Blisterverpackung	in blister packaging		
Umgebungsbedingungen		Environmental conditions	
Schutzart	IP44	Protection type	IP44

Konformität / Approbation**Conformity / Approval****geprüft nach:**

EN 61008-
1:1994+A2+A11, EN
61008 2-1/ 08.94
IEC884-1 A1/ 12.94

Tested in accordance with:

EN 61008-
1:1994+A2+A11, EN
61008 2-1/ 08.94
IEC884-1 A1/ 12.94

