


QualityFlex BB-flex lighting set 5 m, CRI > 80, 9,6 W / m, IP00  
**Artikel-Nr. 15292004**



QualityFlex BB-flex lighting set 5 m, CRI > 80, 9,6 W / m, IP00, 4.100K. LED flex lighting for decorative, technical as well as efficient lighting of light coves, linear applications and backlighting, basic or general lighting of rooms, architectural applications and for areas where high illumination is required, such as indirect or direct lighting, luminous ceilings, gastronomy lighting and much more. Lampenleistung je Meter: 9.6 W/m, Schutzklasse: II, Spannung: 24V , Abstrahlwinkel: 120.0 °, 140 LEDs pro Meter, Chip-Abstand (Short Pitch) : 8,3mm. Zur Individuellen Anwendung kann die LED-Flexplatine alle 50 mm eingekürzt werden. Die maximale Systemlänge von 5.000mm darf mit einer Einspeisung nicht überschritten werden.

<b>Artikel-Nr.</b>	<b>15292004</b>
<b>Stand:</b>	06.12.2021 19:09

Colour temperature	4100 K
Luminous flux	1,020 lm
Beam angle	120 °
Amount of light sources / fittings	700 Qty
Lamp	LED not changeable
scope of delivery	inkl. 1 x LED-Flexplatine, 1 x Netzgerät 50W, 2 x Anschlussleitung separat, 1 x Montageanleitung, 5 x Kennzeichnungsetiketten

Control	on/off
Voltage	24V
Protection class	II
Width	8 mm
Aufbauhöhe	1.5 mm
Circuit type	Parallel conduction