



Housing Color	Grey
Material of Lens	Plastic
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant voltage
Rated Input	2.2 W
Rated Input Voltage	3.7 V/DC
Power Supply Unit incl.	No
Dimmable	No
Motion Detector	No
Accumulator/Battery Operated	Yes
Accumulator/Battery Chemical System	Li-Ion
Number of Accumulator/Battery	1
Type of Accumulator/Battery	Li-Ion battery type 18650
Accumulator/Battery Capacity	2200 mAh
Accumulator/Battery Voltage	3.7 V/DC
Accumulator/Battery Weight	47 g
Accumulator Charging Time min.	6 h
Accumulator Charging Time max.	8 h
Accumulator Charging Time	6-8 h
Accumulator Operating Time	3 h

Width	140 mm
Height	340 mm
Base length	100.5 mm
Base width	100.5 mm
Base height	100.5 mm
Working Temperature	-25 to 45 °C
Storage Temperature	-25 to 45 °C
IP Protection Class	IP 54
Life Time L70 / B50	30000 h

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Rendering Index (Ra)	80
Rated Luminous Flux	170 lm
Rated Angle of Reflection	98 Degree
Light Distribution	Symmetric
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below, Side, Rear
Length	140 mm