

**Artikel Nr.: 930594**

Zubehör, LED-Netzgerät steckerfertig inkl. 3fach Verteiler für Herculis Displayleuchte












IP20 CE

**Elektrische Daten**

Betriebsart	stromkonstant	Eingangsspannung	220-240V AC/50-60Hz
Leistung		Leistungsfaktor	
Ausgangsspannung	2-35V DC	Anschlußmöglichkeit	
Ausgangsstrom	350 mA		

**Produkteigenschaften**

	Schutzklasse II		Überspannungsschutz
SELV	Schutzkleinspannung		Lampenbetriebsgerät 110
	Kurzschlußfest		Möbeleinbau geeignet
	Überlastschutz	ErP	Standby-Stromverbrauch < 0,5 W
	Übertemperaturschutz	LVD	Sicherheit nach EN 61347
	Sicherheitstrafo	EMC	Funkentstörung + Störfestigkeit nach EN 55015 + EN 61547
	nicht dimmbar	EMC	Netzstromoberwellen + Flicker nach EN 61000-3-2 + EN 61000-3-3

Schwarze Felder sind zutreffend / graue Felder sind nicht zutreffend

**Artikel Nr.: 930594**

Zubehör, LED-Netzgerät steckerfertig inkl. 3fach Verteiler für Herculis Displayleuchte

**Abmessungen und Gewicht****Grenzwerte**

Länge	2480,00 mm	Betriebstemperatur	-20°C - +50°C
Breite	20,00 mm	Gehäusetemperatur	0 °C
Höhe	13,00 mm	max. Menge Sicherungsautomaten	
Durchmesser	0,00 mm	max. Einschaltstrom	
Gewicht	165 g	kapazitive Last	

**Article No.: 930594**

Accessories, LED power supply unit ready to plug in incl. 3-way distributor for Hercules display light












IP20 

**Electrical Characteristics**

Operating mode	constant current	Input voltage	220-240V AC/50-60Hz
Power		Power factor	
Output voltage	2-35V DC	Connection possibility	
Output current	350 mA		

**Product features**

 Protection class II	 Overvoltage protection
SELV Low voltage protection	 Lamp control gear 110
 Short circuit protection	 Suitable for furniture installation
 Overload protection	ErP Standby-power consumption < 0,5 W
 Overheating protection	LVD Safety according to EN 61347
 Safety transformer	EMC Interference suppression + immunity according to EN 55015 + EN 61547
 not dimmable	EMC Mains harmonics + flicker according to EN 61000-3-2 + EN 61000-3-3

Black fields are applicable / gray fields are not applicable

**Article No.: 930594**

Accessories, LED power supply unit ready to plug in incl. 3-way distributor for Hercules display light

**Dimensions & Weight****Absolute maximum ratings**

Length	2480,00 mm	Operating temperature	-20°C - +50°C
Width	20,00 mm	Case temperature	0 °C
Height	13,00 mm	max. amount of circuit breakers	
Diameter	0,00 mm	max. inrush current	
Product weight	165 g	capacitive load	