## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: Deko-Light

Supplier's address: Product Management, DEKO-LIGHT Elektronik Vertriebs GmbH Auf der Hub 2 D-76307 Karlsbad

## Model identifier: L840346

## Type of light source:

	Product para		specific dimmers
Anti-glare shield:	Nein	Dimmable:	Only with
High luminance light source:	Nein		
Colour-tuneable light source:	Nein	Envelope:	_
Mains or non-mains:	NMLS	Connected light source (CLS):	Nein
Light source cap-type (or other electric interface)	other elctrical		
Lighting technology used:	LED	Non-directional or directional:	DLS

Product parameters							
Parameter	Value	Parameter	Value				
General product parameters:							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	9	Energy efficiency class	F				
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	728 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000				
On-mode power (P <sub>on</sub> ), expressed in W	9,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00				
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	90				

Outer	Height	2	Spectral power	See image			
dimensions	Width	10	distribution in the	in last page			
without	Depth	500	range 250 nm to 800				
separate			nm, at full-load				
control gear,							
lighting							
control parts							
and non-							
lighting							
control parts, if any							
if any (millimetre)							
	(2)		If use envirolent				
Claim of equiva	lent power(ª)	-	If yes, equivalent power (W)	-			
			Chromaticity	0,382			
			coordinates (x and y)	0,380			
Parameters for directional light sources:							
Peak luminous i	Peak luminous intensity (cd)		Beam angle in	115			
			degrees, or the				
			range of beam				
			angles that can be				
			set				
Parameters for LED and OLED light sources:							
R9 colour rende	ering index value	89	Survival factor	0,90			
the lumen maintenance factor		0,70					
(a),		· · · · · · · · · · · · · · · · · · ·					

(a)'-' : not applicable;

(b)'-' : not applicable;

