



Special features

- Base dia.: 120 mm

| | | | |
|---|---|--------------------------------|-------------|
| Housing Material | Die-cast aluminium | Power Consumption | 7 kWh/1000h |
| Housing Color | Grey | Energy Efficiency Class | G |
| Protection Class | Protection class I/protective grounding | | |
| Rated Input | 6.6 W | | |
| Rated Input Voltage Frequency | 220-240 V/AC 50 / 60 Hz | | |
| Power Supply Unit incl. | Yes | | |
| Connection Type | Clamp | | |
| Dimmable | No | | |
| Motion Detector | No | | |
| Light Source | LED, Light source not changeable | | |
| Color Temperature | 3000 K | | |
| Colour Consistency | 6 SDCM | | |
| Colour Rendering Index (Ra) | 70 | | |
| Rated Luminous Flux | 361 lm | | |
| Light Distribution | Symmetric | | |
| Distribution Characteristic 120° | NDLS | | |
| Light Exit Surfaces | 1 | | |
| Light characteristics | Indirect | | |
| Light direction | Below | | |
| Length | 128.5 mm | | |
| Width | 123 mm | | |
| Height | 800 mm | | |
| Base diameter | 120 mm | | |
| Working Temperature | -20 to 50 °C | | |
| Storage Temperature | -10 to 60 °C | | |
| IP Protection Class | IP 44 | | |
| Life Time L70 / B50 | 25000 h | | |
| Switching Cycles | 100000 | | |