BRUMBERG

FIBATEC LED RGB + W starry sky set

Article no. 48221002

Light. For Generations.





Tende

LED RGB starry sky set. Comprising: 1 x projector - 13.8 W Power-LED (L $270 \times W 155 \times H 100 \text{ mm}$), 1 x radio remote control, 1 x fiber bundle, customised, 200-component: $50 \times \emptyset 1.0 \text{ mm}$, length = 1,000 mm, $50 \times \emptyset 1.0 \text{ mm}$, length = 1,500 mm, $50 \times \emptyset 1.0 \text{ mm}$, length = 2,000 mm, $50 \times \emptyset 1.0 \text{ mm}$, length = 2,500 mm, including 1,500 mm connection cable with Schuko plug, including power supply unit for connection with the 230-V mains voltage, without fan (thus no noise generation), LED color control with radio remote control, radio frequency: 869.5 MHz, transmission power (Ps) &It, 0 dBm, range (visual contact): approximately 5 m, function scope: On / Off, white light selection key (ww / nw / w), RGB color change using a touch wheel, dimmer keys for red / green / blue, dimming of the set light color, option of selecting 10 different color programs . The set has been designed for an area of approximately 4-5 m². Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 8W, Light colour: RGBW, With control gear: Yes, Control: Wireless technology control.

Article data	
Article no.	48221002
GTIN	4251433944546
Series name	FIBATEC
Short description	LED RGB + W starry sky set
Innendurchmesser Faseraufnahme	30 mm
Scope of delivery	Lieferung inkl. RGBW Funkfernbedienung
Weight	3.530 kg
Length of the connection line	1,500 mm

Lighting technology		
Light generator output	8 W	
Colour temperature	RGB+W	
Light colour	RGBW	

BRUMBERG

FIBATEC LED RGB + W starry sky set

Article no. 48221002

Light. For Generations.

Operating technology of the luminaire	
AC nominal voltage max	230 V
Frequenz max.	50 Hz
Lamp	LED
Protection class	
Degree of protection	IP20
Ambient temperature	0 bis 40 °C
Control	Wireless technology control
Length of the connection line	1,500 mm
Bulb change possible	Yes
Radio range	5 m
Transmission frequency	869.5 MHz

Packing data	
Gross weight	4.1 kg
Length of packaging	300 mm
Packaging width	300 mm
Packaging hight	300 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.