

Art no	373801	373802	373803	373901	373950	373951
						
Description	A60 NORMAL 470LM 5,5W E27	A60 NORMAL 806LM 8W E27	A60 NORMAL 1060LM 10,5W E27	B35 CANDLE 250LM 3W E14	P45 BALL 250LM 3W E14	P45 BALL 250LM 3W E27
Lamp power (W)	5,5	8	10,5	3	3	3
Nominal voltage (V)	220-240V 50/60 Hz	220-240V 50/60 Hz	220-240V 50/60 Hz	220-240V 50/60 Hz	220-240V 50/60 Hz	220-240V 50/60 Hz
Supply current (mA)	43mA	72mA	90mA	31mA	31mA	31mA
Inrush current	4.88A	6.24A	6.80A	2.78A	2.78A	2.78A
Rated lifetime (h) L70B50 - Ta 25°C	25000	25000	25000	25000	25000	25000
Number of start-up cycles	40000	40000	40000	40000	40000	40000
Color temperature (K)	2700	2700	2700	2700	2700	2700
Run-up time 60% lumen (s)	<0,1	<0,1	<0,2	<0,2	<0,2	<0,2
Dimmable	No	No	No	No	No	No
Comparison incandescent lamp (W)	40	60	75	25	25	25
Mercury content (mg)	0	0	0	0	0	0
Luminous flux (lm)	470	806	1060	250	250	250
Lm/W (lm)	85	90	100	74	74	74
Lumen maintenance rated lifetime (%)	70	70	70	70	70	70
Power factor	0,5	0,5	0,5	0,4	0,4	0,4
Start-up time (s)	<0,1	<0,1	<0,2	<0,2	<0,2	<0,2
Beam angle (°)	220°	220°	220°	280°	210°	210°
Ra-index	>80	>80	>80	>80	>80	>80
Energy class	F	F	F	G	G	G
Energy consumption (kwh/1000h)	5,5	8	10,5	3	3	3
Ambient temperature	-20°C - +40°C	-20°C - +40°C	-20°C - +40°C	-20°C - +40°C	-20°C - +40°C	-20°C - +40°C
Max lamp length (mm)	102	102	110	102	78	74
Max lamp diameter(mm)	60	60	60	35	45	45
Bulb diameter (mm)	60	60	60	35	45	45
Bulb/lamp material	PC	PC	PC	PC	PC	PC
Base	E27	E27	E27	E14	E14	E27
Packaging unit (pcs)	10	10	10	10	10	10
Lamp weight gross (g)	40	42	58	28	23	23