

Connector - with screwless terminals, lockable



Product description	
BALS-Prd.-Nr	310634
EAN	4024941197533
product category (PG)	Connector QUICK-CONNECT
current (A)	16A
number of poles (P99)	5p
number of poles (P)	3p+N+PE
position of earth contact (H)	6 h
voltage (V)	200/346 up to 240/415V
frequency (HZ)	50 and 60Hz

Product description	
protection degree (SA)	IP44
colour code 1 (KF1)	red RAL 3000
Colour of appliance	Housing cover red RAL 3000, Collar red RAL 3000, Hinged lid red RAL 3000, Cable gland grey RAL 7035
connection design (AT)	screwless spring-clamp technology
maximum conductor size (LQ)	2,5 qmm
cable entry (KE)	Cable gland
Height	155mm
Width	84mm
Depth	91mm
material of enclosure (GM)	Polyamide
contact	The contact carrier is made of polyamide, the contacts are brass nickel plated

Additional technical properties	
	Multi-Grip cable gland with gasket and integrated strain relief, Screwless housing connection with snap fastening, The connector is lockable with the plug art.-no. 210950 and padlock art.no. 580642, For cable diameter from 8 up to max. 18 mm

Logistics data	
Weight/pcs	0.186 kg / Piece
Packaging	Bag
Content amount	1 ST

Logistics data	
EAN	4024941197533
Length	91 mm
Width	84 mm
Height	155 mm
Weight	0.187 kg
Volume	1,184.82 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941835411
Length	258 mm
Width	183 mm
Height	212 mm
Weight	2.012 kg
Volume	8,750 ccm

