



Housing Material	Die-cast aluminium	Life Time L70 / B50	50000 h
Housing Color	Grey	Switching Cycles	50000
Material of Lens	Glass	Power Consumption	8 kWh/1000h
Protection Class	Protection class I/protective grounding	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class D.
Operating Mode	Constant current		
Rated Input	7.4 W		
Rated Input Voltage Frequency	200-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Cable Gland Diameter	12 mm		
Dimmable	No		
Light Source	LED, Light source changeable TC		
Color Temperature	3000/4000 K		
Colour Consistency	3 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	237/256 lm		
Rated Luminous Flux 2	256 lm		
Rated Angle of Reflection	50 Degree		
Rated Angle of Reflection 2	100 Degree		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Length	120 mm		
Width	100 mm		
Height	600 mm		
Working Temperature	-20 to 40 °C		
Storage Temperature	-20 to 50 °C		
IP Protection Class	IP 65		
IK Protection Class	IK06		