lightnet

Matric-SX

Free standing luminaire - Direct/indirect light distribution



Illustrations may only be similar and serve as an orientation.

Matric-SX. LED. Free standing luminaire with one luminaire head. Luminaire body made of high-quality aluminum profile. Surface finish Radiant Silver. Direct/indirect light distribution. Colour temperature: 3500K (Neutral White). Colour Rendering Index (CRI): >80. Lens Louvre: precision lenses with louvre for wide and symmetrical light distribution. High glare limitation, compatible for office applications. UGR<=19. Reflector: Satin Silver. Dimmable. LxWxH (luminaire head, rectangular/Stand). L=1470mm.

W=40mm. H=2200/40mm. Medium-power current. 10300lm. 85W. 19,8kg. Binning initial <= MacAdam 3. U-formed floor base matching luminaire`s outer surface colour. Plug Schuko CEE 7/7 (Type E+F). IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated


Article code: LSXLSX-835M-L1470-UA-A

lightnet

Matric-SX

Free standing luminaire - Direct/indirect light distribution







Article code: LSXLSX-835M-L1470-UA-A

Customer	/ Project:		
Note:			

Productname Matric-SX Lamp LED

Installation Type Free standing luminaire

Surface finish Radiant Silver

Colour temperature 3500K
Colour Rendering Index (CRI) CRI>80
Optical system Lens Louvre

Reflector Colour Inside Reflector: Satin Silver Control Separately dimmable

Length L/Diameter D (mm)

Width W (mm)

Height H (mm)

Current/Power

Luminous Flux

Power consumption

Base-Type

L=1470mm

W=40mm

H=2200/40mm

Medium-Power

10300lm

85W

U-base

Plug Schuko CEE 7/7 (E+F)

Degree of protection IP20

LED lifetime L85B10 (tq 25° C) = 50.000h

UGR UGR<=19
Photometric code 8 35 / 3 3 9

Indoor/Outdoor Indoor: ta [ambient] max. 25°C

Weight (kg) 19,8kg

