



Clear design language, visual highlight! With the BERMUDA light series developed by our designer Johannes Tomm, you can create a comfortable atmosphere far beyond the typical average.

Whether its an elegant wall light, fancy table and standing lamp or even for illuminating your garden– the BERMUDA series lends every lighting situation that special touch.

Special features

- Dimmable using touch sensor
- Swivel-mounted
- 360° light emission angle
- Ready to use

Housing Material	Die-cast aluminium	Height	1708 mm
Housing Color	Black	Diameter	250 mm
Material of Lens	Plastic	Base height	26 mm
Colour of Lens	White	Base diameter	250 mm
		Product weight	3928 g
Protection Class	Protection class II/protective insulation	Working Temperature	-10 to 30 °C
Rated Input	18 W	Storage Temperature	-20 to 60 °C
Rated Input Voltage	100-240 V/AC 50 / 60 Hz	IP Protection Class	IP 20
Frequency			
Power Supply Unit incl.	Yes	Life Time L70 / B50	50000 h
Connection Cable Primary	Yes	Switching Cycles	25000
Primary Connection	Power plug	Power Consumption	18 kWh/1000h
Primary Cable Length	2.1 m	Energy Efficiency Class	G
Connection Type According to Standard	Typ Y		
Dimmable	Yes		
Control technology	Touch-Sensor		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Lightcolor	Warm white (WW)		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	715 lm		
Luminous Efficiency	39.7 lm/W		
Rated Angle of Reflection	360 Degree		
Light Distribution	Symmetric		
Distribution Characteristic 120°	NDLS		
Swivel Angle	30 Degree		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Top, Below, Side		