



This pendant lamp is distinct for its transparent luminous element. The surface is almost completely see-through when switched off. When the light is switched on, the pane distributes the light almost entirely without glare. This pendant lamp is fully office-compatible with a glare value [UGR] of under 19. Bright, efficient and with a sophisticated design, this light stands out in any type of office environment.

Special features

- Very low glare value
- Transparent luminous element
- Max. suspended mounting 1,500 mm

Housing Material	Aluminium	Working Temperature	-10 to 55 °C
Housing Color	White	Storage Temperature	-20 to 60 °C
Material of Lens	PMMA	IP Protection Class	IP 40
Protection Class	Protection class I/protective grounding	IK Protection Class	IK04
Rated Input	50 W	Life Time L70 / B50	75000 h
Rated Power Consumption Standby	0.5 W	Life Time L80 / B10	50000 h
Rated Input Voltage Frequency	200-240 V/AC 50 / 60 Hz	Life Time L80 / B50	60000 h
Power Supply Unit incl.	Yes	Power Consumption	50 kWh/1000h
Connection Type	Clamp	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class C.
Dimmable	Yes		
Control	Leading-edge dimmer, Trailing-edge dimmer		
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Color Temperature	3000/3500/4000 K		
Colour Consistency	5 SDCM		
Colour Rendering Index (Ra)	90		
Rated Luminous Flux	6200/6400/6400 lm		
Rated Angle of Reflection	140 Degree		
Rated Angle of Reflection 2	150 Degree		
UGR	22		
Light Distribution	Symmetric		
Light Exit Surfaces	1		
Light characteristics	Direct, Indirect		
Light direction	Top, Below		
Height	12 mm		
Diameter	633 mm		
Base height	43 mm		
Base diameter	215 mm		
Pendulum Length max.	1800 mm		

