



Product Features

ClassEA iso - jack, shielded, single, flush mounting, with break off metall mounting rings, pure white (similar RAL 9010)

- for use in 10 Gigabit-Ethernet-Networks (transmission bandwidth 500 MHz)
- perfect shielding with closed zinc die cast housing
- variable cable entry (+/-30°)
- 360° shielding and strain relief in one work process
- additional grounding via flat plug possible
- 360° shielding and strain relief in one work process
- additional grounding via flat plug possible
- quick installation via LSA-contacts
- break off mounting ring can be converted into mounting bracket
- latching quick mounting cover
- RJ45-openings slanted downwards
- colour code T568A and T568B according to TIA / EIA-568-B.2
- suitable for Cat.6 and Cat.7 cables (Ø 6-10 mm)
- LSA-contacts for one wire 0,4-0,63 mm Ø, AW 26-22, maximum number of connections > 50-times
- suitable for PoE++ / 4PPoE according to IEEE 802.3bt
- UPOE conform
- HDBaseT conform
- suitable for the UAE-design wall plates of all well-known manufacturer (Berker, Busch-Jäger, GIRA, JUNG, Merten etc.)
- according to the following standards:
- ISO/IEC 11 801, ClassEA, shielded
- DIN EN 50173-1, ClassEA, shielded
- ANSI TIA/EIA-568-C.2, ClassEA
- life > 750 cycles
- RJ11/RJ12-protected against mismatching
- GHMT certified

Features	
General	
Surface	high-gloss
Cover plate	Yes
Centre plate	Yes
Support ring	Yes
Design	jack
Design capability	Yes
Labeling field	Yes
shielded	Yes
Classification	ClassEA iso
PoweroverEthernet	Yes
Protection class IP	21
Halogen Free	Yes
Statistical goods number	85369010
Country of manufacture	DE
GTIN (EAN)	4043921660201
Mounting types	
floor outlet box/underfloor installation	Yes
flush-mounted	Yes
surface-mounted	Yes
trunking installation	Yes
Dimensions/Weights without packaging	
Length mm	80
Width mm	80
Height mm	41
Net weight piece kg	0,129
Certifications	
WEEE	Yes
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	10
Packaging unit Weight kg	1,73
Packaging unit Width mm	312
Packaging unit Height mm	178
Packaging unit Depth mm	87
References	
Accessories	10010001, 10010051, 10010055, 10010056, 13510002, 13510003, 13510052, 13510053, 13510503, 13510505, 13511503, 21207000, 23810106, 238101100, 23810112, 39200000, 39200002
Similar article	136112030, 138104030, 138112070

