

Art no

489003

489004

489013

489014



Description

**AURA LED TCD 7,7W 700LM
3000K 2-PIN G24d-2**
**AURA LED TCD 7,7W 700LM
4000K 2-PIN G24d-2**
**AURA LED TCD 10,5W 1000LM
3000K 2-PIN G24d-3**
**AURA LED TCD 10,5W 1000LM
4000K 2-PIN G24d-3**

Lamp power (W)

7,7

7,7

10,5

10,5

Nominal voltage (V)

220-240V 50/60 Hz

220-240V 50/60 Hz

220-240V 50/60 Hz

220-240V 50/60 Hz

Supply current (mA)

37mA

37mA

51mA

51mA

Rated lifetime (h) L70B50 at 25°C Ta

30000

30000

30000

30000

Number of start-up cycles

>40000

>40000

>40000

>40000

Color temperature (K)

3000

4000

3000

4000

Run-up time 60% lumen (s)

<1

<1

<1

<1

Dimmable

No

No

No

No

Comparison CFL lamp (W)

18

18

26

26

Mercury content (mg)

0

0

0

0

Luminous flux (lm)

700

700

1000

1000

Lm/W (lm)

91

91

95

95

Lumen maintenance rated lifetime (%)

70

70

70

70

Power factor

>0,7

>0,7

>0,7

>0,7

SDCM

<6

<6

<6

<6

Start-up time (s)

<0,5

<0,5

<0,5

<0,5

Beam angle (°)

120°

120°

120°

120°

Burning position

Horizontal

Horizontal

Horizontal

Horizontal

Rotable cap

120°

120°

120°

120°

Ra-index

>80

>80

>80

>80

Energy class

F

F

F

F

Energy consumption (kwh/1000h)

7,7

7,7

10,5

10,5

Ambient operation temperature

-20°C - +40°C

-20°C - +40°C

-20°C - +40°C

-20°C - +40°C

Max lamp length (mm)

134

134

154

154

Max lamp diameter(mm)

33,5

33,5

33,5

33,5

Lamp material

PC

PC

PC

PC

Base

G24d-2

G24d-2

G24d-3

G24d-3

Packaging unit (pcs)

10

10

10

10

Lamp weight gross (g)

75

75

85

85