



The ARCTURUS LED wall-mounted light has a modern cube design [optionally also elongated] and is suitable for flexible lighting outdoors. Using an integrated shutter, the light emission angle of the IP54 light can be adjusted between 0° and 90° in order to generate a different light pattern depending on the requirements of the application. Protected in the dark grey die-cast aluminium housing are the two high-power LEDs, which generate 5.5 W of warm white light.

**Special features**

- Adjustable light emission angle

<b>Housing Material</b>	Die-cast aluminium
<b>Housing Color</b>	Grey
<b>Material of Lens</b>	Glass
<b>Protection Class</b>	Protection class I/protective grounding
<b>Rated Input</b>	6 W
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz
<b>Power Supply Unit incl.</b>	Yes
<b>Connection Type</b>	Clamp
<b>Dimmable</b>	No
<b>Motion Detector</b>	No
<b>Light Source</b>	LED, Light source not changeable
<b>Color Temperature</b>	3000 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	80
<b>Rated Luminous Flux</b>	200 lm
<b>Rated Angle of Reflection</b>	90 Degree
<b>Distribution Characteristic 120°</b>	NDLS
<b>Light Exit Surfaces</b>	2
<b>Light characteristics</b>	Direct, Indirect
<b>Light direction</b>	Top, Below
<b>Length</b>	79 mm
<b>Width</b>	110 mm
<b>Height</b>	172 mm
<b>Base length</b>	68 mm
<b>Base width</b>	110 mm
<b>Base height</b>	110 mm
<b>Working Temperature</b>	-5 to 40 °C
<b>Storage Temperature</b>	-10 to 60 °C
<b>IP Protection Class</b>	IP 54

<b>Life Time L70 / B50</b>	30000 h
<b>Switching Cycles</b>	100000
<b>Power Consumption</b>	6 kWh/1000h
<b>Energy Efficiency Class</b>	G