



The APOLLON narrow, puristic pendant lamp fits into almost any environment seamlessly and in addition to the elegant visual design also delivers a rich warm white light. The APOLLON is available in two different sizes with a matte surface in black and white.

Special features

- Especially narrow design
- High colour rendering
- Suspended mounting up to max. 3,000 mm
- Dimmable

Housing Material	Aluminium	Working Temperature	-20 to 40 °C
Housing Color	Black	Storage Temperature	-30 to 60 °C
Housing Surface	Matt	IP Protection Class	IP 20
Protection Class	Protection class II/protective insulation	Life Time L70 / B50	50000 h
Rated Input	28 W	Switching Cycles	25000
Rated Input Voltage Frequency	200-250 V/AC 50 / 60 Hz	Power Consumption	28 kWh/1000h
Power Supply Unit incl.	Yes	Energy Efficiency Class	G
Connection Type	Clamp		
Dimmable	Yes		
Control technology	Leading-edge dimmer, Trailing-edge dimmer		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	2700 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	90		
Rated Luminous Flux	1755 lm		
Rated Angle of Reflection	110 Degree		
Light Distribution	Symmetric		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	2		
Light characteristics	Direct, Indirect		
Light direction	Top, Below		
Length	1004 mm		
Width	80 mm		
Height	8 mm		
Base length	650 mm		
Base width	35 mm		
Base height	48 mm		
Pendulum Length max.	3000 mm		